

High Speed Oven

Merrychef eikon[•] e1s



Standard Features


- Rapid Cooking Technology combines three heat technologies:
- Tuned Impingement
- Microwave
- Convection
- Ventless cooking capabilities through built-in catalytic converter
- Rapid cooking up to 10-12 times faster than a conventional oven
- 31cm x 31cm (12" x 12") cavity in a 41cm (16") width footprint
- Cool-to-touch exterior
- easyTouch[®], icon driven touchscreen user interface
- Very easy to clean with large rounded edges
- Quiet operation 52 dbA in standby mode
- USB memory stick data transfer of up to 1024 cooking profiles
- Built-in diagnostic testing
- Fits on a 50cm (19.7") worktop and no need for side installation space.
- Black exterior on stainless steel
- Soft edge front design

Specifications

The eikon[®] e1s is the first choice for anyone who wants to prepare fresh, hot food on demand where space is at a premium.

The eikon® e1s is the ideal way to cook, toast, grill, bake and regenerate a wide range of fresh or frozen foods, such as sandwiches, pastries, pizzas, fish, vegetables and meat.

One standard eikon[®] e1s unit runs off a standard domestic 13A-16A supply.



Proiect

Approval_ Date____

• Solid cookplate

Cook plate liner

Solid base basket

• Guarded paddle with supporting side walls

• Other accessories by request

Item _____ Quantity _____ CSI Section 11400

HOW IT WORKS

The convection fan pulls air in through the fan inlet (1). This is then heated and returned to the cavity through the catalytic converters (2) and impinger plate (3) to produce an even heat pattern in the oven. This heat pattern allows food to cook evenly and produces a crisp golden finish, everytime.

CE

Welbilt UK Limited,

Ashbourne House, The Guildway,

Old Portsmouth Road, Guildford, GU3 1LR, United Kingdom Tel: +44(0)1483 464900
Fax: +44(0)1483 464905

www.welbilt.com www.merrvchef.com

eikon[®] e1s



INCLUDED ACCESSORIES

- Solid cook plate
- Paddle with supporting side walls
- Cook plate liner
- Solid base basket

CONSTRUCTION


• Stainless steel cavity and casework (Painted)

MICROWAVE POWER

• Microwave settings, off or 5-100% in 1% increments

CONVECTED HEAT

• Temperature settings OFF and from 100°C to 260° C / 212°F to 500°F in 1°C steps



DIMENSIONS

MODEL	(OVERALL SIZ				
MODEL	HEIGHT	WIDTH	DEPTH	WEIGHT		
eikon® e1s	588 mm (23.2″)	407 mm (16.0")	538 mm (21.2")	NET 46.0 kg (102 lbs) GROSS 56.0 kg (124 lbs)		

POWER REQUIREMENTS & OUTPUT

Merrychef eikon e1s

ELECTRICAL SUPPLY							POWER OUTPUT (APPROX.)			
Country / Region (examples)	Voltage	Arrangement	Connections Used	Plug Current Rating per Phase*	Max. Power Input	Microwave** (IEC 705) 100%	Convected Heat	Combination Mode		
AP/EU	1N~ 200-230 V 50 Hz	Single Phase	L + N + E	16 A	2990 W	800W	2200 W	800 W** + 900 W		
UK	1N~ 200-230 V 50 Hz	Single Phase	L + N + E	13 A	2990 W	800W	2200 W	800 W** + 900 W		



* This is not consumption. ** This is approx. microwave power output.

Welbilt reserves the right to make changes to the design or specifications without prior notice.

Welbilt UK Limited, Ashbourne House, The Guildway,

Old Portsmouth Road,

Guildford, GU3 1LR, United Kingdom

Tel: +44(0)1483 464900
Fax: +44(0)1483 464905

www.welbilt.com www.merrychef.com

